



PRESSURE GAUGE PRICE LIST

R20050501

6786 TIPPERARY
HOUSTON TX, 77061
(800) 901-1316
(713) 643-1022
(713) 643-2855 FAX

www.stewartsusa.com

How to Order by Code Number

- 1 Select **Model** by case & connection size
- 2 Select **Pressure Range**. (by Code)
- 3 Select **Mounting Type**, if other than standard bottom connection.
- 4 Add **Special Configuration**, if needed (by Code or description)
- 5 Add choice of **Liquid Filling**, If appropriate.

Example 1:

Model	Range	Mounting	Special Configuration	Filling Type
40SV	100	FP		

40SV-100-FP

4" 316 SS Case, 1/4" NPT, 316 SS Wetted Parts, VibraGauge® option, Front Flange Panel Mount, Lower Back Connection, 0 - 100 psi

Example 2:

Model	Range	Mounting	Special Configuration	Filling Type
41S	10K			GF

41S-10K-GF

4" 316 SS Case, 1/2" NPT, 316 SS Wetted Parts (Standard Bottom Connection, no code needed); 0 - 10,000 psi, Glycerin Filled

Example 3:

Model	Range	Mounting	Special Configuration	Filling Type
20S	30	LB	B	GF

20S-30-LB-B-GF

2-1/2" 316 SS Case, 1/4" NPT, Lower Back 316SS Wetted Parts, 0 - 30 Psi / Bar Dual Scale, Glycerin filled

Pressure & Vacuum	
CODE	RANGE (psi)
3	0-3
5	0-5
6	0-6
10	0-10
15	0-15
30	0-30
60	0-60
100	0-100
160	0-160
200	0-200
300	0-300
400	0-400
600	0-600
800	0-800
1K	0-1,000
1500	0-1500
2K	0-2,000
3K	0-3,000
4K	0-4,000
5K	0-5,000
6K	0-6,000
10K	0-10,000
15K	0-15,000
20K	0-20,000
30K	0-30,000
35K	0-35,000
50K	0-50,000
60K	0-60,000
V30	30"Hg-0
R315	Receiver 3-15
C15	30"Hg-0-15
C30	30"Hg-0-30
C60	30"Hg-0-60
C100	30"Hg-0-100
C160	30"Hg-0-160
C200	30"Hg-0-200
C300	30"Hg-0-300

Vacuum
Receiver
Compound
Compound
Compound
Compound
Compound
Compound
Compound

Inches of Water Column	
CODE	RANGE
6WC	0-6"
10WC	0-10"
16WC	0-16"
25WC	0-25"
30WC	0-30"
40WC	0-40"
60WC	0-60"
100WC	0-100"
160WC	0-160"
200WC	0-200"
250WC	0-250"
V6-0	VAC 6"-0
V10-0	VAC 10"-0
V16-0	VAC 16"-0
V25-0	VAC 25"-0
V40-0	VAC 40"-0
V60-0	VAC 60"-0
V100-0	VAC 100"-0
V160-0	VAC 160"-0
V200-0	VAC 200"-0
V250-0	VAC 250"-0

Ounce	
CODE	RANGE
10oz	0-10oz
16oz	0-16oz
32oz	0-32oz
40oz	0-40oz
60oz	0-60oz
100oz	0-100oz
160oz	0-160oz

Mounting Types

Description	C.CODE
Center Back Connection	-CB
Lower Back Connection	-LB
Front Flange Panel Mount	-FP
C-Clamp Panel Mount	-C
Rear Flange Wall Mount	-R

Dual Scales

Description	C.CODE
PSI/Bar Dual Scale	-B
PSI/KPA Dual Scale	-K
PSI/KgCm2 Dual Scale	-KGCM2

Special Configurations

Description	C.CODE
Solid Front Safety Case	-S
Monel Wetted Parts	-M
Safety Zone Glow Gauge Reflective	-G

Liquid Filling	Code
Glycerin Filled	-GF
Silicone Filled	-SF
Fluorolube Filled	-FF
VibraGauge® Dampened Movement	V (add to model #)

TABLE OF CONTENTS

	Dial Size	Model	Pressure Gauge Description	PAGE
	4" (100mm)	40S & 41S	316 SS Fillable Case, 316 SS wetted parts, 1/4" & 1/2"	5
	4" (100mm)	44S & 45S	316 SS Non-Fillable Case, 316 SS wetted parts, 1/4" & 1/2"	6
4	4" (100mm)	40B & 41B	316 SS Fillable Case, Brass wetted parts, 1/4" & 1/2"	7
	4" (100mm)	44ST & 45ST	316 SS Non-Fillable Case, 316 SS wetted parts, Test Gauge, 1/4" & 1/2"	8
	4" (100mm)	44BT & 45BT	316 SS Non-Fillable Case, Brass wetted parts, Test Gauge, 1/4" & 1/2"	9
	4" (100mm)	42S & 43S	316 SS Fillable Case, 316 SS wetted parts, Utility Gauge, 1/4" & 1/2"	10
4.5	4-1/2" (130mm)	50S & 51S	Reinforced Thermoplastic Phenolic Case , 316 SS wetted parts, Process Gauge, 1/4" & 1/2"	11
	2-1/2" (63mm)	20S	316 SS Fillable Case, 316 SS wetted parts, 1/4"	12
	2-1/2" (63mm)	20B	316 SS Fillable Case, Brass wetted parts, 1/4"	13
2.5	2-1/2" (63mm)	21S	316 SS Fillable Case, 316 SS wetted parts, Utility Gauge, 1/4"	14
	2-1/2" (63mm)	23B	304 SS Filled Case, Brass wetted parts, Utility Gauge, 1/4"	15
	2-1/2" (63mm)	24B	304 SS Non-Fillable Case, Brass wetted parts, Utility Gauge, 1/4"	16
	2-1/2" (63mm)	25B	Black Steel Non-Fillable Case, Brass wetted parts, Utility Gauge, 1/4"	17
	2" (50mm)	30S	316 SS Fillable Case, 316 SS wetted parts, 1/4" / 1/8"	18
2	2" (50mm)	32B	304 SS Filled Case, Brass wetted parts, Utility Gauge, 1/4" / 1/8"	19
	2" (50mm)	33B	304 SS Non-Fillable Case, Brass wetted parts, Utility Gauge, 1/4" / 1/8"	20
	2" (50mm)	34B	Black Steel Non-Fillable Case, Brass wetted parts, Utility Gauge, 1/4" / 1/8"	21
	1-1/2" (40mm)	10S	316 SS Fillable Case, 316 SS wetted parts, 1/8" / 1/4" (available center back only).....	22
1.5	1-1/2" (40mm)	11B	304 SS Non-Fillable Case, Brass wetted parts, Utility Gauge, 1/8" - 1/4"	23
	1-1/2" (40mm)	12B	Black Steel Non-Fillable Case, Brass wetted parts, Utility Gauge, 1/8" / 1/4".....	24
	1-1/2" (40mm)	13B	304 SS Filled Case, Brass wetted parts, Utility Gauge, 1/8" / 1/4"	25
	6" (160mm)	60S & 61S	316 SS Fillable Case, 316 SS wetted parts, 1/4" & 1/2"	26
	6" (160mm)	62S & 63S	316 SS Non-Fillable Case, 316 SS wetted parts, 1/4" & 1/2"	27
6	6" (160mm)	60B & 61B	316 SS Fillable Case, Brass wetted parts, 1/4" & 1/2"	28
	6" (160mm)	62B & 63B	316 SS Non-Fillable Case, Brass wetted parts, 1/4" & 1/2"	29
	6" (160mm)	62BT & 63BT	316 SS Non-Fillable Case, Brass wetted parts Test Gauge, 1/4" & 1/2"	30
	6" (160mm)	62ST & 63ST	316 SS Non-Fillable Case, 316 wetted parts, Test Gauge, 1/4" & 1/2"	31

A Legacy of Safety, Quality, Reliability.

The Stewart-Buchanan Group of companies has been in existence since 1870 and over the years have established and maintained a reputation for the manufacture of high quality products.

The most comprehensive selections of pressure and temperature instrumentation, valves, manifolds and accessories available from one manufacturer, and are always pleased to discuss and advise on the design and construction of special applications.

Products are manufactured to meet the CE marking requirements of P.E.R.1999 (S2001) and P.E.D. 97/23/EC together with our ISO 9001 approval.

The parent company was formed in 1870 and has seen steady and sustainable growth over the years and is now recognized as one of the leading manufacturers in our particular market with worldwide sales to 50 different countries.

Special Orders and Non-stock items: A minimum order quantity per item may be required for specials and non-stocked items. Consult Stewarts-USA for lead times and additional charges, if any. "Specials" are non-returnable and non-cancelable.

Warranty: Stewarts USA warrants our pressure gauges to be free of defects in material and workmanship for a period of one year from the date of shipment to the original purchaser. Stewarts USA will repair or replace such gauge (F.O.B. Houston, TX USA) should our internal examination reveal it to be defective. Gauge failures determined to be caused by abuse, over-range and incompatibility with environment or process media will not be considered under this warranty. Stewarts USA assumes no other responsibility or liability.

Caution: All Stewarts USA gauges should be carefully selected to meet the demands of the particular application. The information on our literature and brochures is offered only as a guide to assist in making the proper selection. Selection of the proper product, as well as its installation and use, is the sole responsibility of the user. Improper application or product misuse may cause failure of the product, resulting in possible personal injury or property damage. For correct use and application of all Stewarts USA products, please refer to the proper standard as set forth by ASME. These documents may be obtained from the American Society of Mechanical Engineers (ASME). ASME, Three Park Avenue, New York, NY 10016-5990 U.S.A.

Payment Terms: Our Standard terms are NET 30 days. In the event Buyer fails to make full payment when due, Buyer's account can be subject to "Credit Hold" and shipments cannot be released until account is current. Any invoice that remains unpaid is subject to a late payment charge of 1.5% per month, or if such rate is greater than the maximum rate permitted by applicable law, then at the highest rate allowed by applicable law. In addition, if Seller employs an attorney or collection agency to assist in collection of the account, Buyer agrees to pay all of Seller's legal fee(s) and court costs.

Shipping: F.O.B. Houston, TX 77061 U.S.A.

Prices: The information contained in this catalog and on our literature and brochures was correct at the time of printing. Due to the Stewarts-USA commitment of continuous development and improvement, these specifications and prices are subject to change without notice. Any information contained within our literature and brochures should not be interpreted as a contractual agreement by Stewarts-USA. All orders are subject to the approval of Stewarts-USA, LLC.

4" (100mm) ALL STAINLESS STEEL MODEL GAUGE

(Fillable)

Model **40S** (1/4") **41S** (1/2")

Standard Features:

316 SS Case (fillable)	Adjustable Pointer
316 SS Tube & Socket	Accuracy: ± 0.50 %
Top Blowout Relief Grommet	Over 10,000 psi ± 1%
Pulsation Dampened (removable restrictor screw)	Low Pressure ± 1.5%

1.	Pressure 0-15 psi through 0-800 psi, Vacuum and Compound, NH3	\$104.80
2.	0 - 1,000 psi Through 0 - 10,000 psi	\$109.00
3.	0 - 15,000 psi	\$142.65
4.	0 - 20,000 psi Through 0 - 35,000 psi (Available Only with Medium & High Press Conn., model 41S)	\$215.50
5.	Receiver 3-15 psi	\$131.80

Special Configuration and Options: (added to Base Price)

	VibraGauge® Filled Dampened Movement (40S becomes 40SV, 41S becomes 41SV)	\$10.00
1.	Glycerin Filled (add -GF)	\$8.00
2.	Silicone Filled (add -SF)	\$31.70
3.	Lower Back Connection (add -LB)	\$12.50
4.	Panel Mount Front Flange Lower Back Conn. (add -FP)	\$26.70
5.	Rear Flange Mount (add -R)	\$19.40
6.	C - Clamp, Panel Mount, Lower Back Conn. (add -C)	\$41.50
7.	Solid Front / Blow-Out Back, Btm Connection (add -S)	\$21.45
8.	Solid Front / Blow-Out Back, Lower Back Connection Only (add -L, -S)	\$23.10
9.	Front Flange, Btm Conn., Solid Front / Blow-Out Back	\$60.20
10.	Front Flange, Lower Back Conn., Solid Front / Blow-Out Back (add -FP, -S)	\$83.25
11.	Rear Flange, Btm Conn., Solid Front / Blow-Out Back (add -R, -S)	\$47.55
12.	1/4" Medium Pressure Female Conn., (add -1/4MPF)	\$27.15
13.	1/4" High Pressure Female Conn., (1/4HPF)	\$27.15
14.	9/16" Medium Pressure Male Conn., **Btm Only**, (9/16MPM)	\$26.20
15.	9/16" High Pressure Male Conn., **Btm Only **, (9/16HPM)	\$38.10
16.	Max Pressure Pointer (External Reset) Fillable	\$64.80
17.	Max / Minimum Pressure Pointer (External Reset) Fillable	\$100.80
18.	Glow Dial / Reflective Pointer & Safety Zone Green Reflective Tabs (add -G)	\$33.55
19.	Monel 400 Series Bourdon Tube and Connection (lowest range 0-10 psi) (add -M)	\$80.15
20.	Mirror Dial, Knife Edge Pointer	\$25.30
21.	BSP Thread Connection (add -BSPP=parallel, add -BSPT=tapered)	\$5.00
22.	SnubbaGauge® Option (Piston snubber built into socket, 4 pistons for various media viscosities, user changeable)(special order)	\$154.80
23.	Tube Stub connection (special order, delivery times apply)	\$58.56

Items Done at Stewarts USA (Houston)

24.	4-1/2" Adapter Ring (to convert 4" panel mount to 4-1/2" panel hole)	\$36.70
25.	High Temp Lens & Gasket Non Fillable (specify temp)	\$43.40
26.	SS Tags	\$6.00
27.	Cleaned For Oxygen Service (add -O)	Net adder \$10.00
28.	Case Change (+ price of case)	Net adder \$5.00
29.	Calibration Chart (NIST Traceability) Ranges 10 psi - 10,000 psi	Net adder \$25.00
30.	Calibration Chart (NIST Traceability) Ranges 15,000 psi - 40,000 psi	Net adder \$40.00

4" (100mm) ALL STAINLESS STEEL MODEL GAUGE

(Non-Fillable)

Model	44S (1/4")	45S (1/2")
-------	------------	------------

Standard Features:

316 SS Case (Non-fillable)	Adjustable Pointer
316 SS Tube & Socket	Accuracy: ± 0.50%
Back Blowout Relief Grommet	Over 10,000 psi ± 1%
Pulsation Dampened (removable restrictor screw)	Low Pressure: ± 1.5%

1.	Low Pressure Inches of W.C., Vac W.C., Compound W.C., Pressure 3 psi or 5 psi	\$181.60
2.	Pressure 0-10 psi through 0-800 psi, Vac and Compound, NH3	\$97.10
3.	0 - 1,000 psi Through 0 - 10,000 psi	\$101.30
4.	0 - 15,000 psi	\$134.95
5.	0 - 20,000 psi Through 0 - 35,000 psi (Available Only with Medium & High Press Conn., model 45S)	\$207.80
6.	Receiver 3-15 psi	\$124.10

Special Configuration and Options: (added to Base Price)		
--	--	--

1.	VibraGauge® Dampened Movement (44S becomes 44SV, 45S becomes 45SV))	\$10.00
2.	Lower Back Connection (add -LB)	\$12.50
3.	Panel Mount Front Flange Lower Back Conn. (add -FP)	\$26.70
4.	Rear Flange Mount (add -R)	\$19.40
5.	C - Clamp, Panel Mount, Lower Back Conn. (add -C)	\$41.50
6.	Solid Front / Blow-Out Back, Btm Connection (add -S)	\$21.45
7.	Solid Front / Blow-Out Back, Lower Back Connection Only (add -L, -S)	\$23.10
8.	Front Flange, Btm Conn., Solid Front / Blow-Out Back	\$52.50
9.	Front Flange, Lower Back Conn., Solid Front / Blow-Out Back (add -FP, -S)	\$83.25
10.	Rear Flange, Btm Conn., Solid Front / Blow-Out Back (add -R, -S)	\$47.55
11.	1/4" Medium Pressure Female Conn., (add -1/4MPF)	\$27.15
12.	1/4" High Pressure Female Conn., (1/4HPF)	\$27.15
13.	9/16" Medium Pressure Male Conn., **Btm Only**, (9/16MPM)	\$26.20
14.	9/16" High Pressure Male Conn., **Btm Only **, (9/16HPM)	\$38.10
15.	Max Pressure Pointer (External Reset)	\$64.80
16.	Max / Minimum Pressure Pointer (External Reset)	\$100.80
17.	Glow Dial / Reflective Pointer & Safety Zone (add G)	\$33.55
18.	Monel 400 Series Bourdon Tube and Connection (lowest range 0-10 psi)	\$80.15
19.	Mirror Dial, Knife Edge Pointer	\$25.30
20.	BSP Thread Connection	\$5.00

Items Done at Stewarts USA (Houston)		
--------------------------------------	--	--

21.	4-1/2" Adapter Ring (to convert 4" panel mount to 4-1/2" panel hole)	\$36.70
22.	High Temp Lens & Gasket Non Fillable (specify temp)	\$43.40
23.	SS Tags	\$6.00
24.	Cleaned For Oxygen Service (add -O)	\$10.00
25.	Case Change (+ price of case)	\$5.00
26.	Calibration Chart (NIST Traceability) Ranges 10 psi - 10,000 psi	\$25.00
27.	Calibration Chart (NIST Traceability) Ranges 15,000 psi - 40,000 psi	\$40.00

4" (100mm) STAINLESS CASE / BRASS WETTED PARTS MODEL GAUGE

(Fillable)

Model	40B (1/4")	41B (1/2")
Standard Features:	316 SS Case (fillable) Brass Wetted Parts Top Blowout Relief Grommet	Adjustable Pointer Accuracy: ± 0.50 % Low Pressure ± 1.5 % Pulsation Dampened (removable restrictor screw)
1. Pressure 0-10 psi through 0-800 psi, Vac and Compound		\$75.60
2. 0 - 1,000 psi Through 0 - 6,000 psi		\$79.80
3. Receiver 3-15 psi		\$102.60
Special Configuration and Options: (added to Base Price)		
VibraGauge® Dampened Movement (40B becomes 40BV, 41B becomes 41BV)		
		\$10.00
1. Glycerin Filled (add -GF)		\$8.00
2. Silicone Filled (add -SF)		\$31.70
3. Lower Back Connection (add -LB)		\$12.50
4. Panel Mount Front Flange Lower Back Conn. (add -FP)		\$26.70
5. Rear Flange Mount (add -R)		\$19.40
6. C - Clamp, Panel Mount, Lower Back Conn. (add -C)		\$41.50
7. Solid Front / Blow-Out Back, Btm Connection (add -S)		\$21.45
8. Solid Front / Blow-Out Back, Lower Back Connection Only (add -L, -S)		\$23.10
9. Front Flange, Btm Conn., Solid Front / Blow-Out Back		\$52.50
10. Front Flange, Lower Back Conn., Solid Front / Blow-Out Back (add -FP, -S)		\$83.25
11. Rear Flange, Btm Conn., Solid Front / Blow-Out Back (add -R, -S)		\$47.55
12. Max Pressure Pointer (External Reset) Fillable		\$64.80
13. Max / Minimum Pressure Pointer (External Reset) Fillable		\$100.80
14. Mirror Dial, Knife Edge Pointer		\$25.30
15. BSP Thread Connection		\$5.00
Items Done at Stewarts USA (Houston)		
16. 4-1/2" Adapter Ring (to convert 4" panel mount to 4-1/2" panel hole)		\$36.70
17. High Temp Lens & Gasket Non Fillable (specify temp)		\$43.40
18. SS Tags		\$6.00
19. Case Change (+ price of case)	Net adder	\$5.00
20. Calibration Chart (NIST Traceability) Ranges 10 psi - 6,000 psi	Net adder	\$25.00
21. Cleaned For Oxygen Service (add -O)	Net adder	\$10.00

4" (100mm) ALL STAINLESS STEEL TEST MODEL GAUGE

(Test Gauge)

Model	44ST <small>(1/4")</small>	45ST <small>(1/2")</small>
-------	----------------------------	----------------------------

Standard Features:

316 SS Case (Non-Fillable)
 316 SS Wetted Parts
 Back Blowout Relief Grommet

Mirror Dial, Knife Edge Pointer

5 Point Calibration Chart

Accuracy: ± 0.25 of 1% (10,000 psi & Below) (ASME B40.1 Grade 3A)

15,000 psi & over ± 0.50 of 1% (ASME B40.1 Grade 2A)

1.	Pressure 0-10 psi through 0-800 psi, Receiver 3-15 psi, Vac and Compound	\$335.50
2.	0 - 1,000 psi Through 0 - 10,000 psi	\$389.20
3.	0 - 15,000 psi	\$413.20
4.	0 - 20,000 psi Through 0 - 35,000 psi (Available Only with Medium & High Press Conn., model 45ST)	\$809.65

Special Configuration and Options: (added to Base Price)

1.	Lower Back Connection (add -LB)	\$12.50
2.	Panel Mount Front Flange Lower Back Conn. (add -FP)	\$26.70
3.	Rear Flange Mount (add -R)	\$19.40
4.	C - Clamp, Panel Mount, Lower Back Conn. (add -C)	\$41.50
5.	Solid Front / Blow-Out Back, Btm Connection (add -S)	\$21.45
6.	Solid Front / Blow-Out Back, Lower Back Connection Only (add -L, -S)	\$23.10
7.	Front Flange, Btm Conn., Solid Front / Blow-Out Back	\$52.50
8.	Front Flange, Lower Back Conn., Solid Front / Blow-Out Back (add -FP, -S)	\$83.25
9.	Rear Flange, Btm Conn., Solid Front / Blow-Out Back (add -R, -S)	\$47.55
10.	1/4" Medium Pressure Female Conn., (add -1/4MPF)	\$27.15
11.	1/4" High Pressure Female Conn., (add -1/4HPF)	\$27.15
12.	9/16" Medium Pressure Male Conn., **Btm Only**, (add -9/16MPM)	\$26.20
13.	9/16" High Pressure Male Conn., **Btm Only**, (add -9/16HPM)	\$38.10
14.	Max Pressure Pointer (External Reset)	\$64.80
15.	Max / Minimum Pressure Pointer (External Reset)	\$100.80
16.	Perspex Lens with hole opening for pointer adjusting	\$15.00

Items Done at Stewarts USA (Houston)

17.	4-1/2" Adapter Ring (to convert 4" panel mount to 4-1/2" panel hole)	\$36.70
18.	High Temp Lens & Gasket Non Fillable (specify temp)	\$43.40
19.	SS Tags	\$6.00
20.	Cleaned For Oxygen Service (add -O)	Net adder \$10.00
21.	Case Change (+ price of case)	Net adder \$5.00

4" (100mm) STAINLESS CASE/BRASS WETTED PARTS TEST MODEL GAUGE

(Test Gauge)

Model	44BT (1/4")	45BT (1/2")
Standard Features:	316 SS Case (Non-Fillable) Brass Wetted Parts Back Blowout Relief Grommet	Mirror Dial, Knife Edge Pointer Accuracy: ± 0.25 of 1% (ASME B40.1 Grade 3A) 5 Point Calibration Chart
1. Pressure 0-10 psi through 0-800 psi, Receiver 3-15 psi, Vac and Compound		\$287.50
2. 0 - 1,000 psi Through 0 - 6,000 psi		\$341.20
Special Configuration and Options: (added to Base Price)		
1. Lower Back Connection (add -LB)		\$12.50
2. Panel Mount Front Flange Lower Back Conn. (add -FP)		\$26.70
3. Rear Flange Mount (add -R)		\$19.40
4. C - Clamp, Panel Mount, Lower Back Conn. (add -C)		\$41.50
5. Solid Front / Blow-Out Back, Btm Connection (add -S)		\$21.45
6. Solid Front / Blow-Out Back, Lower Back Connection Only (add -L, -S)		\$23.10
7. Front Flange, Btm Conn., Solid Front / Blow-Out Back		\$52.50
8. Front Flange, Lower Back Conn., Solid Front / Blow-Out Back (add -FP, -S)		\$83.25
9. Rear Flange, Btm Conn., Solid Front / Blow-Out Back (add -R, -S)		\$47.55
10. Max Pressure Pointer (External Reset)		\$64.80
11. Max / Minimum Pressure Pointer (External Reset)		\$100.80
12. Perspex Lens with hole opening for pointer adjusting		\$15.00
Items Done at Stewarts USA (Houston)		
13. 4-1/2" Adapter Ring (to convert 4" panel mount to 4-1/2" panel hole)		\$36.70
14. High Temp Lens & Gasket Non Fillable (specify temp)		\$43.40
15. SS Tags		\$6.00
16. Case Change (+ price of case)	Net adder	\$5.00

4" (100mm) ALL STAINLESS STEEL UTILITY MODEL GAUGE

(Fillable)

Model	42S (1/4")	43S (1/2")
Standard Features:	316 SS Tube & Socket 316 SS Case One-Piece Welded Case & Socket (fillable) Top Blowout Relief Grommet Pulsation Dampened (removable restrictor screw)	Black Enamel Aluminum Pointer Accuracy: 2 - 1 - 2%
1. Pressure 0-15 psi through 0-800 psi, Receiver 3-15 psi, Vac and Compound, NH3		\$58.90
2. 0 - 30 psi Through 0 - 1,000 psi		\$58.90
3. 0 - 1,500 psi Through 0 - 10,000 psi		\$63.60
Special Configuration and Options: (added to Base Price)		
1. Glycerin Filled (add -GF)		\$6.00
2. Silicone Filled (add -SF)		\$25.00
3. Center Back Connection (add -CB)		\$0.95
4. Panel Mount Front Flange Center Back Conn. (add -FP)		\$9.50
5. Rear Flange Mount (add -R)		\$15.30
6. C - Clamp, Panel Mount, Center Back Conn. (add -C)		\$9.50
7. BSP Thread Connection		\$5.00
Items Done at Stewarts USA (Houston)		
8. SS Tags		\$6.00
9. Cleaned For Oxygen Service	Net adder	\$10.00
10. Calibration Chart (NIST Traceability) Ranges 10 psi - 10,000 psi	Net adder	\$25.00

4-1/2" (130mm) *PROCESS* GAUGE, SOLID FRONT / BLOWOUT BACK

(Fillable)

Model	50S (1/4")	51S (1/2")
-------	------------	------------

Standard Features:

Molded Fiberglass / Phenolic Case

316 SS Tube & Socket

Solid Front / Blow-out back, Safety case

Laminated Safety Glass Lens

Micrometer Adjustable Pointer

Accuracy: ± 0.5%

1.	6" WC. Through 250"WC, Vac WC, Compound WC. ("WC = Inches of Water Column, low pressure)	\$187.10
2.	Compound, NH3, and Receiver 3-15 psi	\$106.00
3.	Vacuum, 6 psi, 10 psi, Through 600 psi	\$100.00
4.	800 psi Through 10,000 psi	\$110.00
5.	15,000 psi	\$125.00
6.	20,000 psi (available only with 1/4" HPF or 9/16" MPM) (Model 51S)	\$200.00

Special Configuration and Options: (added to Base Price)

1.	VibraGauge® Dampened Movement (Model becomes 50SV or 51SV)	\$10.00
2.	Monel 400 Series Bourdon Tube & Connection (add -M)	\$78.00
3.	Plastic Lens	\$9.90
4.	1/4" High Pressure Female Connection (add - 1/4HPF)	\$27.15
5.	9/16" Medium Pressure Male Connection (add - 9/16MPM)	\$26.20
6.	Maximum Pressure Pointer (External Reset)	\$61.25
7.	BSP Thread Connection	\$5.00
8.	Glow Dial / Reflective Pointer & Safety Zone Green Reflective Tabs (add -G)	\$40.92

Items Done at Stewarts USA (Houston)

9.	SS Tags	\$6.00
10.	Cleaned For Oxygen Service (add -O)	Net adder \$10.00
11.	Calibration Chart (NIST Traceability) Ranges 10 psi - 10,000 psi	Net adder \$25.00
12.	Calibration Chart (NIST Traceability) 15,000 psi	Net adder \$40.00

2-1/2" (63mm) ALL STAINLESS STEEL MODEL GAUGE

(Fillable)

Model 20S (1/4")

Standard Features:

316 SS Case (fillable)
316 SS Tube & Socket
Top Blowout Relief Grommet

Laminated Safety Glass Lens
Pulsation Dampened (removable restrictor screw)
Accuracy: ±1%
±1.5 % Low Pressure & 15K / 20K

1.	Low Pressure W.C., Vac W.C., Compound W.C., Pressure 3 psi or 5 psi	\$150.30
2.	Vacuum, Receiver 3-15 psi, Compound, NH3, 10 psi Through 1,000 psi	\$66.96
3.	0 - 1,500 psi Through 0 - 6,000 psi	\$70.90
4.	0 - 10,000 psi	\$80.04
5.	0 - 15,000 psi	\$109.90
6.	0 - 20,000 psi (available only with 1/4" Medium Pressure Male Connection)	\$109.90

Special Configuration and Options: (added to Base Price)

	VibraGauge® Dampened Movement (20S becomes 20SV)	\$6.00
1.	Glycerin Filled (add -GF)	\$3.00
2.	Silicone Filled (add -SF)	\$6.00
3.	Lower Back Connection (add -LB)	\$4.00
4.	Panel Mount Front Flange Lower Back Conn. (add -FP)	\$12.10
5.	Rear Flange Mount (add -R)	\$10.50
6.	C - Clamp, Panel Mount, Lower Back Conn. (add -C)	\$18.48
7.	SnubbaGauge® Option (Piston snubber built into socket, 4 pistons for various media viscosities, user changeable)(special order)	\$154.80
8.	(" W.C. Model) Front Flange, Panel Mounted	\$13.90
9.	(" W.C. Model) Front Flange, Panel Mounted, U-Clamp Mounting	\$20.70
10.	Solid Front / Blow-Out Back, Btm Connection (add -S)	\$15.00
11.	Solid Front / Blow-Out Back, Lower Back Connection Only (add -L, -S)	\$28.70
12.	Front Flange, Lower Back Conn., Solid Front / Blow-Out Back (add -FP, -S)	\$33.65
13.	Rear Flange, Btm Conn., Solid Front / Blow-Out Back (add -R, -S)	\$25.50
14.	1/4" Medium Pressure Male Conn., (Add -1/4MPM)	\$25.00
15.	1/4" Medium Pressure Male Connection (Monel WETTED PARTS)	\$53.25
16.	Max Pressure Pointer (External Reset) Fillable	\$45.00
17.	Max / Minimum Pressure Pointer Dual (External Reset) Fillable	\$68.00
18.	Glow Dial / Reflective Pointer & Safety Zone Green Reflective Tabs (add -G)	\$22.35
19.	Monel 400 Series Bourdon Tube and Connection (lowest range 0-10 psi) (add -M)	\$28.20
20.	Adjustable Pointer	\$3.50
21.	Plastic Lens	\$2.00
22.	7/16" S.A.E. Straight Thread O-Ring Connection (add -7/16SAE)	\$17.65
23.	BSP Thread Connection	\$5.00

Items Done at Stewarts USA (Houston)

24.	High Temp Lens & Gasket, Non Fillable (specify temp)	\$28.20
25.	SS Tags	\$6.00
26.	Cleaned For Oxygen Service (Add -O)	Net adder \$10.00
27.	Case Change (+ price of case)	Net adder \$5.00
28.	Calibration Chart (NIST Traceability) Ranges 10 psi - 10,000 psi	Net adder \$25.00
29.	Calibration Chart (NIST Traceability) Ranges 15,000 psi - 20,000 psi	Net adder \$40.00

2-1/2" (63mm) STAINLESS CASE / BRASS WETTED PARTS MODEL GAUGE

(Fillable)

Model 20B (1/4")

Standard Features:

316 SS Case (fillable)
 Brass WETTED PARTS
 Top Blowout Relief Grommet

Laminated Safety Glass Lens
 Pulsation Dampened (removable restrictor screw)
Accuracy: ± 1.0%
 ± 1.5% Low Pressure & 15K / 20K

1.	Low Pressure WC., Vac WC, Compound WC, Pressure 3 psi or 5 psi (WC = Inches of Water Column)	\$67.50
2.	Vacuum, Receiver 3-15 psi, Compound, 10 psi Through 1,000 psi	\$43.90
3.	0 - 1,500 psi Through 0 - 6,000 psi	\$47.90

Special Configuration and Options: (added to Base Price)

VibraGauge® Dampened Movement (20B becomes 20BV) (special order)		\$6.00
1.	Glycerin Filled (add -GF)	\$3.00
2.	Silicone Filled (add -SF)	\$6.00
3.	Lower Back Connection (add -LB)	\$4.00
4.	Panel Mount Front Flange Lower Back Conn. (add -FP)	\$12.10
5.	Rear Flange Mount (add -R)	\$10.50
6.	C - Clamp, Panel Mount, Lower Back Conn. (add -C)	\$18.48
7.		
8.	(1" W.C. Model) Front Flange, Panel Mounted	\$13.90
9.	(1" W.C. Model) Front Flange, Panel Mounted, U-Clamp Mounting	\$19.35
10.	Glow Dial / Reflective Pointer & Safety Zone (add -G)	\$22.35
11.	Max Pressure Pointer (External Reset) Fillable	\$45.00
12.	Max / Minimum Pressure Pointer Dual (External Reset) Fillable	\$68.00
13.	Adjustable Pointer	\$3.50
14.	Plastic Lens	\$2.00
15.	7/16" S.A.E. Straight Thread O-Ring Connection (Add -7/16SAE)	\$11.30
16.	BSP Thread Connection	\$5.00

Items Done at Stewarts USA (Houston)

17.	SS Tags	\$6.00
18.	Cleaned For Oxygen Service (add -O)	\$10.00
19.	Case Change (+ price of case)	\$5.00
20.	Calibration Chart (NIST Traceability) Ranges 10 psi - 6,000 psi	\$25.00

2-1/2" (63mm) ALL STAINLESS *UTILITY* MODEL GAUGE

(Fillable)

Model 21S (1/4")

Standard Features:

316 SS WETTED PARTS
 Top Blowout Relief Grommet
 Polycarbonate Lens
 316 SS Case One-Piece Welded Case & Socket (fillable)

Accuracy: 2 - 1 - 2%

Black Enamel Aluminum Pointer
 Pulsation Dampened (removable restrictor screw)

1.	Vacuum, Receiver 3-15 psi, Compound, 15 psi Through 1,000 psi	\$46.90
2.	0 - 1,500 psi Through 0 - 10,000 psi	\$49.25

Special Configuration and Options: (added to Base Price)

1.	Glycerin Filled (add -GF)	\$2.50
2.	Silicone Filled (add -SF)	\$6.00
3.	Lower Back Connection (add -LB)	\$0.95
4.	Panel Mount Front Flange Lower Back Conn. (add -FP)	\$6.85
5.	Rear Flange Mount (add -R)	\$5.90
6.	C - Clamp, Panel Mount, Lower Back Conn. (add -C)	\$9.05
7.		
8.	Center Back Connection (add-CB)	\$12.61
9.	BSP Thread Connection	\$5.00

Items Done at Stewarts USA (Houston)

10.	SS Tags	\$6.00
11.	Cleaned For Oxygen Service (add -O)	Net adder \$10.00
12.	Calibration Chart (NIST Traceability) Ranges 10 psi - 10,000 psi	Net adder \$25.00

2-1/2" (63mm) STAINLESS CASE BRASS WETTED PARTS UTILITY GAUGE

(Standard: Glycerin Filled)

Model 23B (1/4" standard or 1/8" option)

Standard Features:

SS Case (Glycerin Filled Standard)
 Brass Wetted Parts
 Top Blowout Relief Grommet

Polycarbonate Lens
 Black Enamel Aluminum Pointer
Accuracy: 3 - 2 - 3%
Scale: psi/bar x 100 kPa

1.	Vacuum, Receiver 3-15 psi, Compound, 0 - 15 psi	\$19.60
2.	0 - 30 psi Through 0 - 600 psi	\$18.30
3.	0 - 800 psi Through 0 - 5,000 psi	\$19.00
4.	0 - 6,000 psi Through 0 - 10,000 psi	\$20.50

Special Configuration and Options: (added to Base Price)

1.	Center Back Connection (add -CB)	\$1.10
2.	Panel Mount Front Flange Center Back Conn. (add -FP)	\$2.20
3.	C - Clamp, Panel Mount, Center Back Conn. (add -C)	\$3.60

Items Done at Stewarts USA (Houston)

4.	SS Tags	\$6.00
5.	Calibration Chart (NIST Traceability) Ranges 15 psi - 10,000 psi	Net adder \$25.00

2-1/2" (63mm) STAINLESS CASE BRASS WETTED PARTS UTILITY GAUGE

(Dry, Non-Fillable)

Model **24B (1/4" or 1/8")**

Standard Features:

SS Case (Dry, Non - Fillable)
Brass Wetted Parts

Polycarbonate Lens
Black Enamel Aluminum Pointer
Accuracy: 3 - 2 - 3%
Scale: psi/bar x 100 kPa

1.	Vacuum, Receiver 3-15 psi, Compound, 0 - 15 psi	\$11.10
2.	0 - 30 psi Through 0 - 600 psi	\$10.35
3.	0 - 800 psi Through 0 - 5,000 psi	\$11.10
4.	0 - 6,000 psi Through 0 - 10,000 psi	\$13.50

Special Configuration and Options: (added to Base Price)

1.	Center Back Connection (add -CB)	\$0.65
2.	Panel Mount Front Flange Center Back Conn. (add -FP)	\$2.90

Items Done at Stewarts USA (Houston)

4.	SS Tags	\$6.00
5.	Calibration Chart (NIST Traceability) Ranges 15 psi - 10,000 psi	Net adder \$25.00

2-1/2" (63mm) BLACK STEEL CASE BRASS WETTED PARTS UTILITY GAUGE

(Dry, Non-Fillable)

Model 25B (1/4" or 1/8")

Standard Features:

Black Steel Case (Dry, Non - Fillable)
Brass Wetted Parts

Polycarbonate Lens
Black Enamel Aluminum Pointer
Accuracy: 3 - 2 - 3%
Scale: psi/bar x 100 kPa

1.	Vacuum, Receiver 3-15 psi, Compound, 0 - 15 psi	\$9.95
2.	0 - 30 psi Through 0 - 600 psi	\$8.85
3.	0 - 800 psi Through 0 - 5,000 psi	\$9.55
4.	0 - 6,000 psi Through 0 - 10,000 psi	\$12.00

Special Configuration and Options: (added to Base Price)

1.	Center Back Connection (add -CB)	\$0.65
2.	Panel Mount Front Flange Center Back Conn. (add -FP)	\$3.10
3.	C - Clamp, Panel Mount, Center Back Conn. (add -C)	\$5.25

Items Done at Stewarts USA (Houston)

4.	SS Tags	\$6.00
5.	Calibration Chart (NIST Traceability) Ranges 15 psi - 10,000 psi	Net adder \$25.00

2" (50mm) ALL STAINLESS STEEL MODEL GAUGE

(Fillable)

Model 30S (1/4" or 1/8")

Standard Features:

316 SS Case (fillable)
 316 SS Tube & Socket
 Top Blowout Relief Grommet

Laminated Safety Glass Lens
Accuracy: ±1.0%
 Pulsation Dampened (removable restrictor screw)

1.	Vacuum, Receiver 3-15 psi, Compound, 0 - 15 psi	\$63.35
2.	0 - 30 psi Through 0 - 600 psi	\$63.35
3.	0 - 800 psi Through 0 - 1,000 psi	\$63.35
4.	0 - 1,500 psi Through 0 - 6,000 psi	\$65.70
5.	0 - 10,000 psi	\$65.70
6.	0 - 15,000 psi	\$75.10

Special Configuration and Options: (added to Base Price)

1.	Glycerin Filled (add -GF)	\$2.50
2.	Center Back Connection (add -CB)	No Charge
3.	Panel Mount Front Flange Center Back Conn. (add -FP)	\$10.00
4.	C - Clamp, Panel Mount, Center Back Conn. (add -C)	\$16.00
5.	Glow Dial / Reflective Pointer & Safety Zone (add -G)	\$21.85
6.	7/16" S.A.E. Straight Thread O-Ring Connection	\$7.65
7.	1/8" NPT Connection (add -1/8)	No Charge

Items Done at Stewarts USA (Houston)

8.	SS Tags		\$6.00
9.	Cleaned For Oxygen Service (add -O)	Net adder	\$10.00
10.	Calibration Chart (NIST Traceability) Ranges 10 psi - 10,000 psi	Net adder	\$25.00
11.	Calibration Chart (NIST Traceability) Ranges 15,000 psi	Net adder	\$40.00

2" (50mm) STAINLESS CASE BRASS WETTED PARTS UTILITY GAUGE

(Standard Filled)

Model 32B (1/4" or 1/8")

Standard Features:

SS Case (Glycerin Filled Standard)
 Brass Wetted Parts
 Top Blowout Relief Grommet

Polycarbonate Lens
 Black Enamel Aluminum Pointer
Accuracy: 3 - 2 - 3%
Scale: psi/bar x 100 kPa

1.	Vacuum, Receiver 3-15 psi, Compound, 0 - 15 psi	\$19.60
2.	0 - 30 psi Through 0 - 600 psi	\$18.30
3.	0 - 800 psi Through 0 - 5,000 psi	\$19.00

Special Configuration and Options: (added to Base Price)

1.	Center Back Connection (add -CB)	\$1.10
2.	Panel Mount Front Flange Center Back Conn. (add -FP)	\$2.20
3.	C - Clamp, Panel Mount, Center Back Conn. (add -C)	\$3.60

Items Done at Stewarts USA (Houston)

4.	SS Tags	\$6.00
5.	Calibration Chart (NIST Traceability) Ranges 15 psi - 5,000 psi	\$25.00

Net adder

2" (50mm) STAINLESS CASE BRASS WETTED PARTS UTILITY GAUGE

(Dry, Non-Fillable)

Model	33B	(1/4" standard or 1/8")
--------------	------------	-------------------------

Standard Features:

SS Case (Dry, Non - Fillable)
Brass Wetted Parts

Polycarbonate Lens
Black Enamel Aluminum Pointer
Accuracy: 3 - 2 - 3%
Scale: psi/bar x 100 kPa

1.	Vacuum, Receiver 3-15 psi, Compound, 0 - 15 psi	\$10.90
2.	0 - 30 psi Through 0 - 600 psi	\$9.80
3.	0 - 800 psi Through 0 - 5,000 psi	\$10.35

Special Configuration and Options: (added to Base Price)

1.	Center Back Connection (add -CB)	\$0.50
2.	Panel Mount Front Flange Center Back Conn. (add -FP)	\$2.55

Items Done at Stewarts USA (Houston)

4.	SS Tags	\$6.00
5.	Calibration Chart (NIST Traceability) Ranges 15 psi - 5,000 psi	Net adder \$25.00

2" (50mm) BLACK STEEL CASE BRASS WETTED PARTS UTILITY GAUGE

(Dry, Non-Fillable)

Model 34B (1/4" standard or 1/8")

Standard Features:

Black Steel Case (Dry, Non - Fillable)
Brass Wetted Parts

Polycarbonate Lens
Black Enamel Aluminum Pointer
Accuracy: 3 - 2 - 3%
Scale: psi/bar x 100 kPa

1.	Vacuum, Receiver 3-15 psi, Compound, 0 - 15 psi	\$9.30
2.	0 - 30 psi Through 0 - 600 psi	\$8.20
3.	0 - 800 psi Through 0 - 5,000 psi	\$8.75

Special Configuration and Options: (added to Base Price)

1.	Center Back Connection (add -CB)	\$0.50
2.	Panel Mount Front Flange Center Back Conn. (add -FP)	\$2.70
3.	C - Clamp, Panel Mount, Center Back Conn. (add -C)	\$4.70

Items Done at Stewarts USA (Houston)

4.	SS Tags	\$6.00
5.	Calibration Chart (NIST Traceability) Ranges 15 psi - 5,000 psi	Net adder \$25.00

1-1/2" (40mm) ALL STAINLESS STEEL MODEL GAUGE

(Fillable)

Model 10S (1/8" npt standard. 1/4" npt available in center-back connection only)

Standard Features:

Stainless Case (fillable*)
 316 SS Tube & Socket
 Top Blowout Relief Grommet

Polycarbonate Lens
 Crimped-On Bezel
Scale: psi/bar x 100 kPa
Accuracy: 3 - 2 - 3%
 *(**Note:** Center-Back, "Positioner Gauge", is Dry & Non-fillable)

1.	Vacuum, Receiver 3-15 psi, Compound, 0 - 15 psi	\$22.40
2.	0 - 30 psi Through 0 - 600 psi	\$22.40
3.	0 - 800 psi Through 0 - 1,000 psi	\$25.36
4.	0 - 1,500 psi Through 0 - 6,000 psi	\$30.00
5.	0 - 10,000 psi	\$33.00

Special Configuration and Options: (added to Base Price)

1.	Glycerin Filled (add -GF) (* Not available on "positiner" gauge)	\$2.50
2.	Center-Back Connection (add -CB)	\$3.50
3.	Panel Mount Front Flange Center Back Conn. (add -FP)	\$8.70
4.	C - Clamp, Panel Mount, Center Back Conn. (add -C)	\$15.30
5.	1/4" NPT - Available in center-back connection only. (add -1/4") see Center-Back adder above	\$0.71

Items Done at Stewarts USA (Houston)

6.	SS Tags	\$6.00
7.	Cleaned For Oxygen Service (add -O)	Net adder \$10.00
8.	Calibration Chart (NIST Traceability) Ranges 10 psi - 10,000 psi	Net adder \$25.00

1-1/2" (40mm) STAINLESS CASE BRASS WETTED PARTS UTILITY GAUGE

(Dry, Non-Fillable)

Model 11B (1/8" standard or 1/4" option)

Standard Features:

SS Case (Dry, Non - Fillable)
Brass Wetted Parts

Polycarbonate Lens
Accuracy: 3 - 2 - 3%
Scale: psi/bar x 100 kPa

1.	Vacuum, Receiver 3-15 psi, Compound, 0 - 15 psi	\$10.90
2.	0 - 30 psi Through 0 - 600 psi	\$9.80
3.	0 - 800 psi Through 0 - 5,000 psi	\$10.35
Special Configuration and Options: (added to Base Price)		
1.	Center Back Connection (add -CB)	\$0.50
2.	Panel Mount Front Flange Center Back Conn. (add -FP)	\$2.70
Items Done at Stewarts USA (Houston)		
3.	SS Tags	\$6.00

1-1/2" (40mm) BLACK STEEL CASE BRASS WETTED PARTS UTILITY GAUGE

(Dry, Non-Fillable)

Model 12B (1/8" standard or 1/4")

Standard Features:

Black Steel Case (Dry, Non - Fillable)
Brass Wetted Parts

Polycarbonate Lens

Accuracy: 3 - 2 - 3%

Scale: psi/bar x 100 kPa

1.	Vacuum, Receiver 3-15 psi, Compound, 0 - 15 psi	\$9.30
2.	0 - 30 psi Through 0 - 600 psi	\$8.20
3.	0 - 800 psi Through 0 - 5,000 psi	\$8.75
Special Configuration and Options: (added to Base Price)		
1.	Center Back Connection (add -CB)	\$0.50
2.	Panel Mount Front Flange Center Back Conn. (add -FP)	\$2.70
3.	C - Clamp, Panel Mount, Center Back Conn. (add -C)	\$4.70
Items Done at Stewarts USA (Houston)		
4.	SS Tags	\$6.00

1-1/2" (40mm) STAINLESS CASE BRASS WETTED PARTS UTILITY GAUGE
 (PRE-FILLED)

Model 13B (1/8" standard or 1/4")

Standard Features:

Stainless Case (Glycerin Filled)
 Brass Wetted Parts

Polycarbonate Lens
Accuracy: 3 - 2 - 3%
Scale: psi/bar x 100 kPa

1.	Vacuum, Receiver 3-15 psi, Compound, 0 - 15 psi	\$18.00
2.	0 - 30 psi Through 0 - 600 psi	\$18.00
3.	0 - 800 psi Through 0 - 5,000 psi	\$18.00
Special Configuration and Options: (added to Base Price)		
1.	Center Back Connection (add -CB)	\$0.50
2.	Panel Mount Front Flange Center Back Conn. (add -FP)	\$2.70
Items Done at Stewarts USA (Houston)		
3.	SS Tags	\$6.00

6" (160mm) ALL STAINLESS STEEL MODEL GAUGE

(Fillable)

Model	60S (1/4")	61S (1/2")
Standard Features:		Adjustable Pointer
	316 SS Case (fillable)	Laminated Safety Glass Lens
	316 SS Tube & Socket	Accuracy: ± 0.5 of 1%
	Top Blowout Relief Grommet	Over 10,000 psi ±1.0%
	Pulsation Dampened (restrictor screw)	Low Pressure ±1.5%
1.	Pressure 0-15 psi through 0-800 psi, Receiver 3-15 psi, Vacuum and Compound, NH3	\$166.30
2.	0 - 1,000 psi Through 0 - 10,000 psi	\$173.70
3.	0 - 15,000 psi	\$209.80
4.	0 - 20,000 psi Through 0 - 35,000 psi (Available Only with Medium & High Press Conn., model 61S)	\$303.10
5.	0 - 40,000 psi and 0 - 50,000 psi (Includes SF/BOB Case 1/4"HPF Conn.)	\$930.05
6.	0 - 60,000 psi (Includes SF/BOB Case 1/4"HPF Conn.)	\$948.85
Special Configuration and Options: (added to Base Price)		
	VibraGauge® Dampened Movement (add V to model, 60S = 60SV, 61S = 61SV)	\$10.00
1.	Glycerin Filled (add -GF)	\$23.00
2.	Silicone Filled (add -SF)	\$44.71
3.	Lower Back Connection (add -LB)	\$27.05
4.	Panel Mount Front Flange Lower Back Conn. (add -FP)	\$64.90
5.	Rear Flange Mount (add -R)	\$33.15
6.	C - Clamp, Panel Mount, Lower Back Conn. (add -C)	\$96.40
7.	Solid Front / Blow-Out Back, Btm Connection (add -S)	\$122.80
8.	Solid Front / Blow-Out Back, Lower Back Connection Only (add -LB, -S)	\$165.35
9.	Front Flange, Btm Conn., Solid Front / Blow-Out Back	\$187.75
10.	Front Flange, Lower Back Conn., Solid Front / Blow-Out Back (add -FP, -S)	\$224.14
11.	Rear Flange, Btm Conn., Solid Front / Blow-Out Back (add -R, -S)	\$176.15
12.	1/4" Medium Pressure Female Conn., (add -1/4MPF)	\$27.15
13.	1/4" High Pressure Female Conn., (add -1/4HPF)	\$27.15
14.	9/16" Medium Pressure Male Conn., **Btm Only**, (add -9/16MPM)	\$26.20
15.	9/16" High Pressure Male Conn., **Btm Only **, (add -9/16HPM)	\$38.10
16.	Max Pressure Pointer (External Reset) Fillable	\$76.15
17.	Max / Minimum Pressure Pointer (External Reset) Fillable	\$115.00
18.	Glow Dial / Reflective Pointer & Safety Zone Green Reflective Tabs (add -G)	\$46.52
19.	Monel 400 Series Bourdon Tube and Connection (lowest range 0-10 psi) (add - M)	\$111.20
20.	Mirror Dial with Knife Edge Pointer	\$93.30
21.	BSP Thread Connection (add BSPP=parallel, BSPT=tapered)	\$5.00
22.	SnubbaGauge® Option (Piston snubber built into socket, 4 pistons for various media viscosities, user changeable)(special order)	\$154.80
23.	Tube Stub connection (special order, delivery times apply)	\$66.32
Items Done at Stewarts USA (Houston)		
24.	High Temp Lens & Gasket Non Fillable (specify temp)	\$65.95
25.	SS Tags	\$6.00
26.	Cleaned For Oxygen Service (add -O)	Net adder \$10.00
27.	Case Change (+ price of case)	Net adder \$5.00
28.	Calibration Chart (NIST Traceability) Ranges 10 psi - 10,000 psi	Net adder \$25.00
29.	Calibration Chart (NIST Traceability) Ranges 15,000 psi - 40,000 psi	Net adder \$40.00

6" (160mm) ALL STAINLESS STEEL MODEL GAUGE

(Dry, Non-Fillable)

Model	62S (1/4")	63S (1/2")
Standard Features:		Adjustable Pointer
	316 SS Case	Laminated Safety Glass Lens
	316 SS Tube & Socket	Accuracy: ± 0.5 of 1%
	Back Blowout Relief	Over 10,000 psi ±1.0%
	Pulsation Dampened (restrictor screw)	Low Pressure ±1.5%
1.	Low Pressure W.C., Vac W.C., Compound W.C., Pressure 3 psi or 5 psi	\$259.30
2.	Pressure 0-10 psi through 0-800 psi, Receiver 3-15 psi, Vac and Compound	\$152.65
3.	0 - 1,000 psi Through 0 - 10,000 psi	\$160.05
4.	0 - 15,000 psi	\$196.15
Special Configuration and Options: (added to Base Price)		
1.	VibraGauge® Dampened Movement (62S becomes 62SV, 63S becomes 63SV)	\$10.00
2.	Lower Back Connection (add -LB)	\$27.05
3.	Panel Mount Front Flange Lower Back Conn. (add -FP)	\$64.90
4.	Rear Flange Mount (add -R)	\$33.15
5.	C - Clamp, Panel Mount, Lower Back Conn. (add -C)	\$96.40
6.	Solid Front / Blow-Out Back, Btm Connection (add -S)	\$122.80
7.	Solid Front / Blow-Out Back, Lower Back Connection Only (add -L, -S)	\$165.35
8.	Front Flange, Btm Conn., Solid Front / Blow-Out Back	\$187.75
9.	Front Flange, Lower Back Conn., Solid Front / Blow-Out Back (add -FP, -S)	\$224.14
10.	Rear Flange, Btm Conn., Solid Front / Blow-Out Back (add -R, -S)	\$176.15
11.	Max Pressure Pointer (External Reset)	\$76.15
12.	Max / Minimum Pressure Pointer (External Reset)	\$115.00
13.	Monel 400 Series Bourdon Tube and Connection (lowest range 0-10 psi) (add - M)	\$111.20
14.	Mirror Dial with Knife Edge Pointer	\$93.30
15.	BSP Thread Connection	\$5.00
Items Done at Stewarts USA (Houston)		
16.	High Temp Lens & Gasket Non Fillable (specify temp)	\$65.95
17.	SS Tags	\$6.00
18.	Cleaned For Oxygen Service (add -O)	Net adder \$10.00
19.	Case Change (+ price of case)	Net adder \$5.00
20.	Calibration Chart (NIST Traceability) Ranges 10 psi - 10,000 psi	Net adder \$25.00
21.	Calibration Chart (NIST Traceability) Ranges 15,000 psi - 40,000 psi	Net adder \$40.00

6" (160mm) STAINLESS CASE/BRASS WETTED PARTS MODEL GAUGE

(Fillable)

Model	60B (1/4")	61B (1/2")
Standard Features:	316 SS Case (fillable) Brass Wetted Parts Top Blowout Relief Grommet Pulsation Dampened (restrictor screw)	Adjustable Pointer Laminated Safety Glass Lens Accuracy: ± 0.5 of 1% Over 10,000 psi ±1.0% Low Pressure ±1.5%
1.	Pressure 0-10 psi through 0-800 psi, Receiver 3-15 psi, Vac and Compound	\$106.59
2.	0 - 1,000 psi Through 0 - 6,000 psi	\$112.52
Special Configuration and Options: (added to Base Price)		
	VibraGauge® Dampened Movement (60B becomes 60BV, 61B becomes 61BV)	\$10.00
1.	Glycerin Filled (add -GF)	\$23.00
2.	Silicone Filled (add -SF)	\$44.71
3.	Panel Mount Front Flange Lower Back Conn. (add -FP)	\$64.90
4.	Rear Flange Mount (add -R)	\$33.15
5.	C - Clamp, Panel Mount, Lower Back Conn. (add -C)	\$96.40
6.	Solid Front / Blow-Out Back, Btm Connection (add -S)	\$122.80
7.	Solid Front / Blow-Out Back, Lower Back Connection Only (add -L, -S)	\$165.35
8.	Front Flange, Btm Conn., Solid Front / Blow-Out Back	\$187.75
9.	Front Flange, Lower Back Conn., Solid Front / Blow-Out Back (add -FP, -S)	\$224.14
10.	Rear Flange, Btm Conn., Solid Front / Blow-Out Back (add -R, -S)	\$176.15
11.	Max Pressure Pointer (External Reset) Fillable	\$76.15
12.	Max / Minimum Pressure Pointer (External Reset) Fillable	\$115.00
13.	Mirror Dial with Knife Edge Pointer	\$93.30
14.	BSP Thread Connection	\$5.00
Items Done at Stewarts USA (Houston)		
15.	SS Tags	\$6.00
16.	Case Change (+ price of case)	Net adder \$5.00
17.	Calibration Chart (NIST Traceability) Ranges 10 psi - 6,000 psi	Net adder \$25.00

6" (160mm) STAINLESS CASE/BRASS WETTED PARTS MODEL GAUGE

(Dry, Non-Fillable)

Model	62B (1/4")	63B (1/2")
Standard Features:	316 SS Case Brass Wetted Parts Top Blowout Relief Grommet Pulsation Dampened (restrictor screw)	Adjustable Pointer Laminated Safety Glass Lens Accuracy: ± 0.5 of 1% Over 10,000 psi ±1.0% Low Pressure ±1.5%
1.	Low Pressure W.C., Vac W.C., Compound W.C., Pressure 3 psi 5 psi	\$212.09
2.	Pressure 0-10 psi through 0-800 psi, Receiver 3-15 psi, Vac and Compound	\$92.95
3.	0 - 1,000 psi Through 0 - 6,000 psi	\$98.86
Special Configuration and Options: (added to Base Price)		
	VibraGauge® Dampened Movement (62B becomes 62BV, 63B becomes 63BV)	\$10.00
1.	Lower Back Connection (add -LB)	\$27.05
2.	Panel Mount Front Flange Lower Back Conn. (add -FP)	\$64.90
3.	Rear Flange Mount (add -R)	\$33.15
4.	C - Clamp, Panel Mount, Lower Back Conn. (add -C)	\$96.40
5.	Solid Front / Blow-Out Back, Btm Connection (add -S)	\$122.80
6.	Solid Front / Blow-Out Back, Lower Back Connection Only (add -L, -S)	\$165.35
7.	Front Flange, Btm Conn., Solid Front / Blow-Out Back	\$187.75
8.	Front Flange, Lower Back Conn., Solid Front / Blow-Out Back (add -FP, -S)	\$224.14
9.	Rear Flange, Btm Conn., Solid Front / Blow-Out Back (add -R, -S)	\$176.15
10.	Max Pressure Pointer (External Reset)	\$76.15
11.	Max / Minimum Pressure Pointer (External Reset)	\$115.00
12.	Mirror Dial with Knife Edge Pointer	\$93.30
13.	BSP Thread Connection	\$5.00
Items Done at Stewarts USA (Houston)		
14.	SS Tags	\$6.00
15.	Case Change (+ price of case)	Net adder \$5.00
16.	Calibration Chart (NIST Traceability) Ranges 10 psi - 6,000 psi	Net adder \$25.00

6" (160mm) STAINLESS CASE/BRASS WETTED PARTS TEST MODEL GAUGE

(Test Gauge)

Model	62BT (1/4")	63BT (1/2")
Standard Features:	316 SS Case (Non-Fillable) Brass Wetted Parts (UP TO 6K) Back Blowout Relief Grommet	Mirror Dial, Knife Edge Pointer 5 Point Calibration Chart Accuracy: ±0.25 of 1% (10,000 psi & Below) (ASME B40.1 Grade 3A) Accuracy: ±0.50 of 1% (15,000 psi & Above) (ASME B40.1 Grade 2A)
1. Vacuum, 10 psi, 15 psi, and 30 psi		\$493.60
2. 0 - 60 psi through 0 - 1,000 psi		\$466.20
3. 0 - 1,500 psi through 0 - 6,000 psi		\$514.20
Special Configuration and Options: (added to Base Price)		
1. Lower Back Connection (add -LB)		\$13.00
2. Panel Mount Front Flange. (add -FP)		\$42.30
3. Rear Flange Mount (add -R)		\$10.00
4. Solid Front / Blow-Out Back, Btm Connection (add -S)		\$122.80
5. Solid Front / Blow-Out Back, Lower Back Connection Only (add -L, -S)		\$165.35
6. Front Flange, Btm Conn., Solid Front / Blow-Out Back		\$187.75
7. Front Flange, Lower Back Conn., Solid Front / Blow-Out Back (add -FP, -S)		\$224.14
8. Rear Flange, Btm Conn., Solid Front / Blow-Out Back (add -R, -S)		\$176.15
9. Max Pressure Pointer (External Reset)		\$76.15
10. Perspex Lens with hole opening for pointer adjusting		\$22.00
Items Done at Stewarts USA (Houston)		
11. SS Tags		\$6.00

6" (160mm) STAINLESS CASE/SS WETTED PARTS TEST MODEL GAUGE

(Test Gauge)

Model	62ST <small>(1/4")</small>	63ST <small>(1/2")</small>
Standard Features: 316 SS Case (Non-Fillable) 316 SS WETTED PARTS Back Blowout Relief Grommet		Mirror Dial, Knife Edge Pointer 5 Point Calibration Chart Accuracy: ±0.25 of 1% (10,000 psi & Below) (ASME B40.1 Grade 3A) Accuracy: ±0.50 of 1% (15,000 psi & Above) (ASME B40.1 Grade 2A)
1. Vacuum, 10 psi, 15 psi, and 30 psi		\$578.20
2. 0 - 60 psi through 0 - 1,000 psi		\$578.20
3. 0 - 1,500 psi through 0 - 6,000 psi		\$578.20
4. 0 - 10,000		\$628.90
5. 0 - 15,000 psi through 0 - 30,000 psi (ss WETTED PARTS) (Available Only with Medium & High Press Conn..)		\$1,049.35
Special Configuration and Options: (added to Base Price)		
1. Lower Back Connection (add -LB)		\$13.00
2. Panel Mount Front Flange. (add -FP)		\$42.30
3. Rear Flange Mount (add -R)		\$10.00
4. Solid Front / Blow-Out Back, Btm Connection (add -S)		\$122.80
5. Solid Front / Blow-Out Back, Lower Back Connection Only (add -L, -S)		\$165.35
6. Front Flange, Btm Conn., Solid Front / Blow-Out Back		\$187.75
7. Front Flange, Lower Back Conn., Solid Front / Blow-Out Back (add -FP, -S)		\$224.14
8. Rear Flange, Btm Conn., Solid Front / Blow-Out Back (add -R, -S)		\$176.15
9. Max Pressure Pointer (External Reset)		\$76.15
10. Perspex Lens with hole opening for pointer adjusting		\$22.00
Items Done at Stewarts USA (Houston)		
11. SS Tags		\$6.00

SUSAPL 20050501