



# STEWARTS-USA, LLC

## Bimetal Thermometers

### NEW ORLEANS

P.O. Box 10646  
 New Orleans, LA 70181-0646 USA  
 504-737-3551  
 504-737-3558 Fax

### HOUSTON

6786 Tipperary  
 Houston, TX 77061 USA  
 713-643-1022  
 713-643-2855 Fax

Price List SUSA200504

Example: **S4210 04 59**

CODE	LENGTH	RANGE
<b>S4210</b>	<b>4</b>	<b>07</b>

5" Face Adjustable Angle, 1/2" NPT Conn., 4" Stem Length, 50/550 F - 10/150 C

### ADJUSTABLE ANGLE INDUSTRIAL THERMOMETERS

304 SS External Parts, Glass Lens and 1/2" npt

		Standard Stem Lengths and Diameters													
		.250" Diameter Stem								.375" Diameter Stem					
Dial Size	Code	2 1/2", 4", 6" or 9"	12"	15"	18"	24"	30"	36"	42"	48"	54"	60"	66"	72"	
3"	<b>S4110</b>	\$88.68	96.8	103.29	109.78	121.67	133.57	145.47	157.36	171.42	185.48	199.54	213.6	227.66	
5"	<b>S4210</b>	\$107.61	115.19	121.67	128.16	140.16	151.96	163.85	175.75	189.81	203.87	217.93	231.99	246.05	

### BACK CONNECTION INDUSTRIAL THERMOMETERS

304 SS External Parts, Glass Lens and 1/2" npt

		Standard Stem Lengths and Diameters													
		.250" Diameter Stem								.375" Diameter Stem					
Dial Size	Code	2 1/2", 4", 6" or 9"	12"	15"	18"	24"	30"	36"	42"	48"	54"	60"	66"	72"	
3"	<b>S3310</b>	\$41.10	47.05	53.54	60.03	71.93	83.82	95.72	107.61						
5"	<b>S3710</b>	\$65.16	70.84	77.33	83.82	95.72	107.61	119.51	131.41						

#### NOTES:

Accuracy +/- 1% full span per ASME B40.3 Grade A.

For Non-standard stem lengths, use next highest price shown in chart.

For Stem lengths over 72" (.375" diameter ONLY) Request Quote

(available up to 120")

316 SS Request Quote

1/2" BSPT connection can be substituted at no charge

\*\* For Stocking or Order Qty's above 20 Units -- Call For Additional Discount Pricing

\*\* Stewarts-USA maintains a constant effort to upgrade and improve its products, therefore prices are subject to change without notice.

## OPTIONS - ADDED TO LIST PRICE

**LENS:**

- Glass - Tempered
- Glass - Shatterproof
- Plastic- Acrylic
- Plastic- Polycarbonate

**Dial Sizes**

3"	5"
\$4.20	\$5.78
\$7.09	\$9.19
\$3.41	\$6.56
\$5.51	\$7.61

**Notes:**

Glass is standard on temperature ranges above 300 F (150 C)

---

**CONNECTIONS:**

- Plain bushing or NPT Conn., smaller than 1/2" where not standard
- Union Conn., - 3" or 5", Industrial Models
- Sliding Compression Fittings, Male or Female

**304 SS List Price adder**

- \$5.78
  - \$26.78
  - Req. Quote
- 

**SILICONE FILL:**

- 3" Back Connected
- 5" Back Connected
- 3" or 5" Adjustable Angle

**List adder**

- \$29.93
- \$35.18
- \$39.38

**Important Notes:**

- Minimum Range -50 F (-45 C) and Maximum Range 500 F (250 C).
  - Polycarbonate lens is standard and included in price adder.
  - Maximum case Temperature not to Exceed 300 F (150 C)
- 

**DIALS AND RANGES:**

- Custom designed dials (Name / Logo / Zones / Color)
- Non-Standard temperature ranges
- Glow Dial for S4110 & S4210

**List adder**

- Req. Quote
- Req. Quote
- \$45.00

**Standard Ranges and Stem Lengths**

Code: S3310, S3710, S4110 & S4210

Length	Code	Temp Code	Dual Scale	
			Fahrenheit	Celsius
2.5"	02	02	-40/160	-40/70
4"	04	17	0/200	-10/90
6"	06	14	0/250	-20/120
9"	09	07	50/300	10/150
12"	12	09	50/550	15/285
15"	15	10	150/750	50/400
18"	18	11	*200/1000	*100/550

**NOTES:** Additional Ranges Available - Consult Factory

24"

24