

PANEL MOUNT

STEWARTS-USA / McDaniel Part Numbers Crossover (316SS)

MODEL 20S (2.5") 316 SS WETTED PARTS

2.5" Dial, 316 SS Wetted Parts, 316 SS Case* Heavy Duty, 1/4" NPT Lower Back Connection, Front Flange Panel Mount									
	McDaniel	Stewarts-USA	McDaniel	Stewarts-USA	Stewarts-USA	DIAL	PRESSURE	NPT	WETTED
	Part # (Dry)	PART # (DRY)	Part # (Glycerin filled)	PART # (Glycerin filled)	PART # (VibraGauge®)	SIZE	RANGE	SIZE	PARTS
1	KSP	20S-V30-FP	KSP-GF	20S-V30-FP-GF	20SV-V30-FP	2.5	30"Hg-0 Vac	1/4"	316 SS
2	KUP	20S-C15-FP	KUP-GF	20S-C15-FP-GF	20SV-C15-FP	2.5	30"Hg-0-15 PSI	1/4"	316 SS
3	KVP	20S-C30-FP	KVP-GF	20S-C30-FP-GF	20SV-C30-FP	2.5	30"Hg-0-30 PSI	1/4"	316 SS
4	KWP	20S-C60-FP	KWP-GF	20S-C60-FP-GF	20SV-C60-FP	2.5	30"Hg-0-60 PSI	1/4"	316 SS
5	KXP	20S-C100-FP	KXP-GF	20S-C100-FP-GF	20SV-C100-FP	2.5	30"Hg-0-100 PSI	1/4"	316 SS
6	KYP	20S-C160-FP	KYP-GF	20S-C160-FP-GF	20SV-C160-FP	2.5	30"Hg-0-160 PSI	1/4"	316 SS
7	K2kP	20S-C200-FP	K2kP-GF	20S-C200-FP-GF	20SV-C200-FP	2.5	30"Hg-0-200 PSI	1/4"	316 SS
8	KZP	20S-C300-FP	KZP-GF	20S-C300-FP-GF	20SV-C300-FP	2.5	30"Hg-0-300 PSI	1/4"	316 SS
9	KTP	20S-R315-FP	KTP-GF	20S-R315-FP-GF	20SV-R315-FP	2.5	3 - 15 Receiver	1/4"	316 SS
12	K10P	20S-10-FP	K10P-GF	20S-10-FP-GF	20SV-10-FP	2.5	0-10 PSI	1/4"	316 SS
13	KAP	20S-15-FP	KAP-GF	20S-15-FP-GF	20SV-15-FP	2.5	0-15 PSI	1/4"	316 SS
14	KBP	20S-30-FP	KBP-GF	20S-30-FP-GF	20SV-30-FP	2.5	0-30 PSI	1/4"	316 SS
15	KCP	20S-60-FP	KCP-GF	20S-60-FP-GF	20SV-60-FP	2.5	0-60 PSI	1/4"	316 SS
16	KDP	20S-100-FP	KDP-GF	20S-100-FP-GF	20SV-100-FP	2.5	0-100 PSI	1/4"	316 SS
17	KEP	20S-160-FP	KEP-GF	20S-160-FP-GF	20SV-160-FP	2.5	0-160 PSI	1/4"	316 SS
18	KFP	20S-200-FP	KFP-GF	20S-200-FP-GF	20SV-200-FP	2.5	0-200 PSI	1/4"	316 SS
19	KGP	20S-300-FP	KGP-GF	20S-300-FP-GF	20SV-300-FP	2.5	0-300 PSI	1/4"	316 SS
20	KHP	20S-400-FP	KHP-GF	20S-400-FP-GF	20SV-400-FP	2.5	0-400 PSI	1/4"	316 SS
21	KIP	20S-600-FP	KIP-GF	20S-600-FP-GF	20SV-600-FP	2.5	0-600 PSI	1/4"	316 SS
22	KJP	20S-800-FP	KJP-GF	20S-800-FP-GF	20SV-800-FP	2.5	0-800 PSI	1/4"	316 SS
23	KKP	20S-1K-FP	KKP-GF	20S-1K-FP-GF	20SV-1K-FP	2.5	0-1000 PSI	1/4"	316 SS
24	KLP	20S-1500-FP	KLP-GF	20S-1500-FP-GF	20SV-1500-FP	2.5	0-1500 PSI	1/4"	316 SS
25	KMP	20S-2K-FP	KMP-GF	20S-2K-FP-GF	20SV-2K-FP	2.5	0-2000 PSI	1/4"	316 SS
26	KNP	20S-3K-FP	KNP-GF	20S-3K-FP-GF	20SV-3K-FP	2.5	0-3000 PSI	1/4"	316 SS
27	K4kP	20S-4K-FP	K4kP-GF	20S-4K-FP-GF	20SV-4K-FP	2.5	0-4000 PSI	1/4"	316 SS
28	KOP	20S-5K-FP	KOP-GF	20S-5K-FP-GF	20SV-5K-FP	2.5	0-5000 PSI	1/4"	316 SS
29	K6kP	20S-6K-FP	K6kP-GF	20S-6K-FP-GF	20SV-6K-FP	2.5	0-6000 PSI	1/4"	316 SS
30	KPP	20S-10K-FP	KPP-GF	20S-10K-FP-GF	20SV-10K-FP	2.5	0-10,000 PSI	1/4"	316 SS
31	KQP	20S-15K-FP	KQP-GF	20S-15K-FP-GF	20SV-15K-FP	2.5	0-15,000 PSI	1/4"	316 SS
32	KRP1/4MPM	20S-20K-FP-1/4MPM	KRP1/4MPM-GF	20S-20K-FP-1/4MPM-GF	20SV-20K-FP-1/4MPM	2.5	0-20,000 PSI	1/4" MPM	316 SS

*McDaniel Case is 304 SS, Stewarts-USA is 316 SS standard.



(For Dual-Scale Ranges)

BAR: -B

KPa: -K

Add above code after -FP.

Example: **20S-600-FP-B-GF**



STEWARTS-USA GAUGE SPECS (Model 20S):

2.5 inch dial

316 SS case

316 SS Wetted Parts

1/4" npt lower back

Front Flange Panel Mount

Repairable

[VibraGauge® Optional: Dampened movement, instead of liquid filling.](#)

ASME Grade 1A 1% full scale accuracy

Laminated Safety Glass Lens

White aluminum dial, black figures

Filled or Fillable

Restrictor Screw standard (removable)

Rolled Threads

For vibration & pulsation.